

PRODUCT NO.	DSHP08TJGET
RoHS compliant	

1

2

3

4

5

6

REV.	ECN NO.	DR	DATE







NOTES :1.Specification:

- 1>.Operating force:1000gf Max
- 2>.Operating Temperature: -40° to+85°
- 3>.Storage Temperature: -40° to+85°
- 4>.Electrical life:1000cycles 25mA 24VDC
- 5>.Mechanical Life:3000cycles Operations


2. PLATING:
GOLD FLASH 1u"(min.) SOLDERAL,
3u" GOLD PLATING ON THE CONTACT AREA,
WITH 50u" NICKEL UNDERPLATINGOVERALL.
3. PART NUMBER DESCRIPTION :

DSHP XX I S G E I

- [包装方式: T=管装 R=Reel]
- [电镀层: F=镀镍3u"焊脚部1.2u" G=镀镍3u"焊脚部3u" R=镀镍10u"焊脚部10u"
- [G=镀金 S=内镀金(接触部)外镀锡(焊脚部)]
- [脚型: S脚 / J脚 / 埋脚 / A脚 / Z脚]
- [T=低推粘性 S=低推不粘性 L=长推]
- [产品参数: 02=2P 04=4P 06=6P 08=8P 10=10P 12=12P]



RECOMMENDED P.C.B. LAYOUT (TOP VIEW)



Number	Part Name	Material	Finished
①	Actuator	UL94 V0	White
②	Cover	UL94 V0	Black
③	Movable	Beryllium Copper	3u" Gold
④	Terminal	Brass	1u" Gold
⑤	Base	UL94 V0	Black
⑥	Terminal Contact	Brass	3u" Gold
⑦	Mylar	UL94 V0	0.05mm

TOLERANCE UNLESS OTHERWISE SPECIFIED		INSPECTION COPY	
LINER	ANGLES	PROJECTION	COPY
0 ± 0.25	0 ± 2'	0 ± 0.15	0 ± 1'
0.00± 0.10	.00± 0.5'	DESIGN	03/20/12
DRAWING		PRAT NO.	DSHP08TJGET
CHECK		FILE NO.	DSHP08TJGET-A
APPRO.		SIZE	UNIT
A4		mm	SCALE
		Z : 1	SHEET
		TOP:1	REV.
			A

總營精密電子股份有限公司
DongGuan Kingtek Industrial Co., Ltd.

BY DSHF SERIES PITCH 1.27mm
PRODUCT FAMILY DSHF SERIES

D

C

B

A

5

6